MODEL SERIES WFPF1300, WFPF13003B

Universal Whole House Filtration System

Replacement Cartridges: WFPFC300, WFPFC400, WFPFC500, WFPFC800, WFPFC900 Series

COMPONENT

Tested and Certified by Water Quality Association (WQA) against NSF/ANSI Standard 42 for materials safety and structural integrity requirements only.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after this filter system. Maximum operating temperature 38º C/100º F. Operating pressure 30-100 psi/207-690 kPa.

CAUTION

READ BEFORE INSTALLING!

A pressure regulator **must be installed** before the filter, if water pressure will at any time exceed the

MAXIMUM RATING OF 100 PSI (690 kPa).

It is recommended that the pressure regulator be set at 75 psi (517 kPa) or less. This will guard against the pressure exceeding the maximum rating at any time.

Protect against freezing. Failure to do so may result in cracking and leakage.

Do not install outdoors in direct sunlight.

Do not install filter in applications where failure or leakage would cause damage.

NOTICE: We strongly recommend that the entire filter system be replaced every 5 years to guard against leaks caused by wear and tear.

828-449-1040 Service Requests/Product Information
800-441-7515 Safety/Health Questions
Protect Plus, LLC Hickory, NC 28601 USA
www.waterfiltration.DuPont.com

P